

Package: repurrrsive (via r-universe)

July 2, 2024

Title Examples of Recursive Lists and Nested or Split Data Frames

Version 1.1.0.9000

Description Recursive lists in the form of R objects, 'JSON', and 'XML', for use in teaching and examples. Examples include color palettes, Game of Thrones characters, 'GitHub' users and repositories, music collections, and entities from the Star Wars universe. Data from the 'gapminder' package is also included, as a simple data frame and in nested and split forms.

License CC0

URL <https://jennybc.github.io/repurrrsive/>,
<https://github.com/jennybc/repurrrsive>

BugReports <https://github.com/jennybc/repurrrsive/issues>

Depends R (>= 2.10)

Imports tibble, utils

Suggests jsonlite, testthat (>= 3.0.0), xml2

Config/Needs/website dplyr, purrr, tidyr

Config/testthat/edition 3

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

Repository <https://jennybc.r-universe.dev>

RemoteUrl <https://github.com/jennybc/repurrrsive>

RemoteRef HEAD

RemoteSha 617365735dc60675f42218b820ae9e971ee026b7

Contents

discog	2
discog_json	3
gap_simple	3
gh_repos	4
gh_users	5
gh_users_json	5
gmaps_cities	6
got_chars	7
got_chars_json	8
sw_people	8
wesanderson	10
wesanderson_json	10
Index	12

discog	<i>Sharla Gelfand's music collection</i>
--------	--

Description

A music collection, as represented in a recursive list returned from the Discogs API.

Usage

```
discog
```

Format

A unnamed list with 155 components, each representing an item in Sharla's music collection.

Source

- Data retrieved on 2019-07-15 from <https://www.discogs.com>
- Original blog post by Sharla Gelfand <https://sharla.party/post/discog-purrr/>

See Also

Other Discogs data and functions: [discog_json\(\)](#)

Examples

```
length(discog)

str(discog, max.level = 2, list.len = 2)

vapply(discog[1:6], `[`, c("basic_information", "title"), FUN.VALUE = "")
```

discog_json	<i>Path to Discogs data as JSON</i>
-------------	-------------------------------------

Description

Path to Discogs data as JSON

Usage

```
discog_json()
```

Value

Local path to JSON file containing Discogs data

See Also

Other Discogs data and functions: [discog](#)

Examples

```
discog_json()
if (require("jsonlite")) {
  d <- fromJSON(discog_json(), simplifyVector = FALSE)
  identical(discog, d)
}
```

gap_simple	<i>Gapminder data frame in various forms</i>
------------	--

Description

The main data frame from the gapminder package in three forms:

1. `gap_simple`, same as `gapminder::gapminder`
2. `gap_nested`, nested by country and continent
3. `gap_split`, split by country

Usage

```
gap_simple
```

```
gap_nested
```

```
gap_split
```

Format

An object of class `tbl_df` (inherits from `tbl`, `data.frame`) with 1704 rows and 6 columns.

Examples

```
gap_simple
gap_nested

str(gap_split, max.level = 1, list.len = 10)
str(gap_split[[1]])
```

gh_repos

GitHub repos

Description

Info on GitHub repos, retrieved from the GitHub API.

Usage

```
gh_repos
```

Format

A unnamed list with 6 components, each itself a list of 30 repos for a specific GitHub user. Each repo's component is a list of length >60, containing information such as name, owner (a list), fork status, and creation date.

Source

<https://developer.github.com/v3/repos/#list-user-repositories>

See Also

Other GitHub data and functions: [gh_users_json\(\)](#), [gh_users](#)

Examples

```
str(gh_repos, max.level = 1)
str(gh_repos[[1]], max.level = 1)
str(gh_repos[[1]][[1]])

str(lapply(gh_repos[[1]][1:3], `[,`, c("full_name", "created_at")))
```

`gh_users`*GitHub users*

Description

Info on GitHub users, retrieved from the GitHub API.

Usage`gh_users`**Format**

A unnamed list with 6 components, each representing a GitHub user. Each user's component is a list of length 30, containing information such as username, GitHub id, and join date.

Source

<https://developer.github.com/v3/users/#get-a-single-user>

See Also

Other GitHub data and functions: [gh_repos](#), [gh_users_json\(\)](#)

Examples

```
str(gh_users, max.level = 1)
str(gh_users[[1]])

str(lapply(gh_users, `[`, c("login", "name")))
```

`gh_users_json`*Paths to GitHub data as JSON and XML*

Description

Paths to GitHub data as JSON and XML

Usage`gh_users_json()``gh_repos_json()``gh_users_xml()``gh_repos_xml()`

Value

Local path to JSON or XML file containing GitHub data

See Also

Other GitHub data and functions: [gh_repos](#), [gh_users](#)

Examples

```
gh_users_json()
if (require("jsonlite")) {
  ghuj <- fromJSON(gh_users_json(), simplifyDataFrame = FALSE)
  identical(gh_users, ghuj)
}
gh_repos_json()
if (require("jsonlite")) {
  ghrj <- fromJSON(gh_repos_json(), simplifyDataFrame = FALSE)
  identical(gh_repos, ghrj)
}
gh_users_xml()
if (require("xml2")) {
  xml <- read_xml(gh_users_xml())
  xml
}
gh_repos_xml()
if (require("xml2")) {
  xml <- read_xml(gh_repos_xml())
  xml
}
```

gmaps_cities

Geocoded cities from Google Maps

Description

This tibble contains the results of geocoding five cities ("Houston", "Washington", "New York", "Chicago", "Arlington") using the Google Maps API on 2022-06-08. Two cities, Washington and Arlington, were deliberately picked for their ambiguity: Washington could refer to the city or the state, and Arlington could mean the one in Virginia or the one in Texas.

Usage

```
gmaps_cities
```

Format

A tibble with 5 rows and two columns. `city` gives the original search term and `json` gives the returned JSON converted to a list.

Source

<https://developers.google.com/maps/documentation/geocoding>

Examples

```
gmaps_cities
```

got_chars

Game of Thrones POV characters

Description

Info on the point-of-view (POV) characters from the first five books in the Song of Ice and Fire series by George R. R. Martin. Retrieved from An API Of Ice And Fire.

Usage

```
got_chars
```

Format

A unnamed list with 30 components, each representing a POV character. Each character's component is a named list of length 18, containing information such as name, aliases, and house allegiances.

Source

<https://anapioficeandfire.com>

See Also

Other Game of Thrones data and functions: [got_chars_json\(\)](#)

Examples

```
str(got_chars, max.level = 1, list.len = 10)
str(got_chars[[1]])
str(lapply(got_chars, `[`, c("name", "culture")))
```

got_chars_json *Paths to Game of Thrones data as JSON and XML*

Description

Paths to Game of Thrones data as JSON and XML

Usage

```
got_chars_json()
```

```
got_chars_xml()
```

Value

Local path to JSON or XML file containing Game of Thrones data

See Also

Other Game of Thrones data and functions: [got_chars](#)

Examples

```
got_chars_json()
if (require("jsonlite")) {
  gotcj <- fromJSON(got_chars_json(), simplifyDataFrame = FALSE)
  identical(got_chars, gotcj)
}
got_chars_xml()
if (require("xml2")) {
  xml <- read_xml(got_chars_xml())
  xml
}
```

sw_people *Entities from the Star Wars Universe*

Description

Data retrieved from the swapi API on the Star Wars Universe.

Usage

```
sw_people  
  
sw_films  
  
sw_planets  
  
sw_species  
  
sw_vehicles  
  
sw_starships
```

Format

Unnamed lists with varying number of components.

Details

- sw_people List of individual people or characters within the Star Wars universe.
- sw_starships List of transport crafts with hyperdrive capability.
- sw_vehicles List of transport crafts without hyperdrive capability.
- sw_films List of Star Wars films.
- sw_species List of types of people or characters within the Star Wars Universe.
- sw_planets List of large masses, planets or planetoids in the Star Wars Universe, at the time of 0 ABY.

Source

Data originally obtained from <http://swapi.co/> using the `rwars` package: <https://github.com/Ironholds/rwars>. The Star Wars API appears to have moved to <https://pipedream.com/apps/swapi> since that time.

Examples

```
# sw_people  
str(sw_people, max.level = 1)  
str(sw_people[[1]])  
sapply(sw_people, `[`, "name")  
  
# sw_films  
str(sw_films, max.level = 1)  
str(sw_films[[1]])  
sapply(sw_films, `[`, "title")
```

wesanderson

Color palettes from Wes Anderson movies

Description

A list of color palettes inspired by Wes Anderson movies, taken from the from [wesanderson](#) package.

Usage

```
wesanderson
```

Format

A named list with 15 components, each containing a color palette from a specific movie. Each palette consists of 4 or 5 hexadecimal color values.

Source

<https://cran.r-project.org/package=wesanderson>

<http://wesandersonpalettes.tumblr.com>

See Also

Other wesanderson data and functions: [wesanderson_json\(\)](#)

Examples

```
str(wesanderson)
```

wesanderson_json

Path to wesanderson JSON and XML

Description

Path to wesanderson JSON and XML

Usage

```
wesanderson_json()
```

```
wesanderson_xml()
```

Value

Local path to JSON or XML file containing Wes Anderson color palettes

See Also

Other wesanderson data and functions: [wesanderson](#)

Examples

```
wesanderson_json()
if (require("jsonlite")) {
  jsonlite::fromJSON(wesanderson_json())
}
wesanderson_xml()
if (require("xml2")) {
  xml2::read_xml(wesanderson_xml())
}
```

Index

* Discogs data and functions

discog, 2
discog_json, 3

* Game of Thrones data and functions

got_chars, 7
got_chars_json, 8

* GitHub data and functions

gh_repos, 4
gh_users, 5
gh_users_json, 5

* datasets

discog, 2
gap_simple, 3
gh_repos, 4
gh_users, 5
gmaps_cities, 6
got_chars, 7
sw_people, 8
wesanderson, 10

* wesanderson data and functions

wesanderson, 10
wesanderson_json, 10

discog, 2, 3
discog_json, 2, 3

gap_nested (gap_simple), 3
gap_simple, 3
gap_split (gap_simple), 3
gh_repos, 4, 5, 6
gh_repos_json (gh_users_json), 5
gh_repos_xml (gh_users_json), 5
gh_users, 4, 5, 6
gh_users_json, 4, 5, 5
gh_users_xml (gh_users_json), 5
gmaps_cities, 6
got_chars, 7, 8
got_chars_json, 7, 8
got_chars_xml (got_chars_json), 8

sw_films (sw_people), 8
sw_people, 8
sw_planets (sw_people), 8
sw_species (sw_people), 8
sw_starships (sw_people), 8
sw_vehicles (sw_people), 8

wesanderson, 10, 10, 11
wesanderson_json, 10, 10
wesanderson_xml (wesanderson_json), 10